



CE



Produktseite

## BATTERY CHARGER DIGITAL GDB 24V / 12V-200 Art.-Nr.: 85128

- Simply connect the charger, select charging mode and the intelligent charging technology does the rest
- For all standard **12V and 24 V battery types**
- Direct charging of a battery connected in the vehicle
- Battery **-saving 10-step charging process**
- Fully automatic, microprocessor-controlled diagnostic, rescue, loading and maintenance function
- Safety features: Overload, short circuit, overheat, reverse polarity and spark and electronic safe
- Rescue function, especially for deep-discharged batteries, is activated as low as 1.5V
- Jump-start function up to **200A**
- LED display
- Display of charging voltage (volts), charging current (ampere) and charging progress (in%)
- Battery types: **PB, GEL, AGM, MF, WET**
- Insulated pliers
- Mobile

**PB** - lead-acid battery

**GEL** - gel battery

**AGM** - Flow battery (start-stop automatic)

**MF** - maintenance-free battery

**WET** - wet batterie

### Technical information:

Rated voltage:	230 V
Frequency:	50 Hz
Output voltage:	12 / 24 V
Fuse rating,:	16 A
Rated power:	6000 W
Effective charging current:	5/15/30/40 A
Batteriekapazität:	20-450 Ah
Number fuse:	10 Stk.
Fuse:	50 A
Starting assistance 1.5 V:	200 A
Battery start without pre-charge:	35 - 50 Ah
Battery Start with pre-charge:	65 - 100 Ah
Maße LxBxH:	297 x 295 x 670 mm
Net. weight:	16,5 kg
Gross weight:	18 kg
Item number:	85128



VE 16



L 355 x B 315 x H 655 mm

GTIN-Code

4015671966445