



CE



Produktseite

BATTERY CHARGER DIGITAL GDB 24V / 12V-250 Art.-Nr.: 85129

- Simply connect the charger, select charging mode and the intelligent charging technology does the rest
- For all standard **12V and 24 V battery types**
- Direct charging of a battery connected in the vehicle
- Battery **-saving 10-step charging process**
- Fully automatic, microprocessor-controlled diagnostic, rescue, loading and maintenance function
- Safety features: Overload, short circuit, overheat, reverse polarity and spark and electronic safe
- Rescue function, especially for deep-discharged batteries, is activated as low as 1.5V
- **Jump** -start function up to **250A**
- LED display
- Display of charging voltage (volts), charging current (ampere) and charging progress (in%)
- Battery types: **PB, GEL, AGM, MF, WET**
- Insulated pliers
- Mobile

PB - lead-acid battery

GEL - gel battery

AGM - Flow battery (start-stop automatic)

MF - maintenance-free battery

WET - wet batterie

Technical information:

Rated voltage:	230 V
Frequency:	50 Hz
Output voltage:	12 / 24 V
Fuse rating,:	16 A
Rated power:	6000 W
Effective charging current:	10/20/35/50 A
Batteriekapazität:	20-550 Ah
Number fuse:	10 Stk.
Fuse:	100 A
Starting assistance 1.5 V:	250 A
Maße LxBxH:	304 x 295 x 674 mm
Net. weight:	19 kg
Gross weight:	20 kg
Item number:	85129



VE 16



L 350 x B 315 x H 680 mm

GTIN-Code

4015671966421