

# zappi

## ➤ Charge your EV with your PV



zappi has 3 charging modes which makes it great for all homeowners. Those with grid-tied micro-generation systems like wind or solar can use the eco settings allowing users to save on energy bills. The charging current is automatically and continually adjusted in response to on-site generation and household power consumption. In FAST charge mode, zappi operates like an ordinary EV charging station.

➤ 7kw Single Phase

➤ 22kw 3-Phase

EV Charging From Surplus Solar Or Wind Generation

Dynamic Load Balancing For Maximum Installation Flexibility

Advanced Integral Safety Features

### 💡 zappi Features

- 3 Charging Modes: ECO, ECO + & FAST
- Optimises Microgeneration Self-Consumption
- Works With Solar PV Or Wind Turbine Systems
- Economy Tariff Sense Input
- Programmable Timer Function
- Charge & Event Logging
- Pin-code Lock Function
- OLEV (Home/Work Scheme) Approved - HUB required
- Tap Operated Display Backlight
- Built-in RCD Protection
- Integral Cable Holster
- Remote Control & Monitoring Add-on Option
- Supplied With Clip-on Grid Current Sensor(s)
- Works Alongside Battery Storage Systems
- A Future Proof Installation
- 3 Year Warranty

### 🔋 Charging Modes

#### ECO 🌱

Charge power is continuously adjusted in response to changes in generation or power consumption elsewhere in the home. Charging will continue until the vehicle is fully charged, even if power is drawn from the grid.

#### ECO + ☀️

Charge power is continuously adjusted in response to changes in generation or power consumption elsewhere in the home. Charging will pause if there is too much imported power, continuing only when there is surplus free power available.

#### FAST 🚗

In this mode, the vehicle will be charged at maximum power. This is just like an ordinary Mode 3 charging point.

## Performance

Mounting Location	Indoor or Outdoor (permanent mounting)
Charging	Mode 3 (IEC 61851-1 compliant communication protocol)
Display	Graphical backlit LCD
Front	LED Multicolour, according to charge status and current
Charging Current	6A to 32A (variable)
Dynamic Load Balancing	Optional setting to limit current drawn from the unit supply or the grid
Connector Type	Type 2 tethered cable (6.5m) or type 2 socket with locking system
Charging Profile	3 charging modes: ECO, ECO+ & FAST
Compliance	LVD 2014/35/EU, EMC 2014/30/EU, EN 62196, EN 62955:2018 CE certified

## Electrical Specs

Rated Power	7kW (1-ph) or 22kW (3-ph)
Rated Supply Voltage	230V AC Single Phase or 400V AC 3-phase (+/- 10%)
Supply Frequency	50 Hz
Rated Current	32A max
Standby Power Consumption	3W
Integral Earth Leakage Protection	30mA Type A RCD (EN 61008) + 6mA DC protection (EN 62955)
Economy Tariff Sense	Input 230V AC sensing (4.0kV isolated)
Wireless Interface	868 MHz (proprietary protocol) for wireless sensor & remote monitoring options
Grid Current Sensor	100A max. primary current, 16mm max. cable diameter
Cable Entry	Rear, bottom or side

## Mechanical Specs

Enclosure Dimensions	439 x 282 x 122mm
Protection Degree	IP65 (weatherproof)
Enclosure Material	ASA
Operating Temperature	25°C to +40°C

## Installation Requirements

Circuit Breaker	32A Curve B
Earthing Arrangement	TN : can be connected to the PME supply. Complies with BS7671:2018-amd1:2020 722.411.4.1 (v) TT : earth resistance < 200 Ω according to BS 7671:2018, or < 100 Ω for some vehicles

## Model Variations

Model No.	Rating	Connector	Colour	
ZAPPI-207UW	7kW	Untethered	White	○
ZAPPI-207TW	7kw	Tethered	White	○
ZAPPI-207UB	7kW	Untethered	Black	●
ZAPPI-207TB	7kW	Tethered	Black	●
ZAPPI-222UW	22kW (3-phase)	Untethered	White	○
ZAPPI-222TW	22kW (3-phase)	Tethered	White	○
ZAPPI-222UB	22kW (3-phase)	Untethered	Black	●
ZAPPI-222TB	22kW (3-phase)	Tethered	Black	●